

FOF ROOF WINDOW



FOF ROOF WINDOW

Applicable

In public and residential buildings

In heated, inhabited rooms

In roof pitch range of 15°- 90°

Suitable on all common roofings with proper flashing

Features

Centre pivot

Slim frame

Toughened glass

Elegant bottom handle

Two passive ventilation positions via handle

Easy installation

10 year guarantee

Material | Wood and finishing

Kiln-dried laminated pine wood

Timber from FSC certified sources

Fungicide protection

Water based lacquer

Cover parts

Aluminium, lacquered, RAL 7043

Handle

Ergonomically designed moulded zinc handle, lacquered

Hinge

Pivot hinge

VARIANT

B700

Pane

Construction 4-16-4H

24 mm double glazing

Low E

Gas (argon)

Toughened glass

U_g (W/m²K) 1.1

Total solar energy transmittance 0.60

U_w (W/m²K) 1.5

Water tightness E1200

Air permeability Class 4

Resistance to wind load Class C4

Sound reduction 32 (-1,-5) dB

Colour

Natural wood

MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
FOF C2R B700	55 x 72 cm	55,0 cm	71,9 cm	39,8 cm	59,0 cm	37,3 cm	53,1 cm	0,198
FOF F6R B700	66 x 112 cm	66,0 cm	111,9 cm	50,8 cm	99,0 cm	48,3 cm	93,1 cm	0,449
FOF M4R B700	78 x 92 cm	78,0 cm	91,9 cm	62,8 cm	79,0 cm	60,3 cm	73,1 cm	0,440
FOF M6R B700	78 x 112 cm	78,0 cm	111,9 cm	62,8 cm	99,0 cm	60,3 cm	93,1 cm	0,561
FOF M8R B700	78 x 134 cm	78,0 cm	133,9 cm	62,8 cm	121,0 cm	60,3 cm	115,1 cm	0,694
FOF S6R B700	114 x 112 cm	114,0 cm	111,9 cm	98,8 cm	99,0 cm	96,3 cm	93,1 cm	0,896

COMPATIBILITY TABLE

SIZE CODE	FLASHING 16-50 MM	FLASHING 16-120 MM 0-16 mm with modifications	AWNING BLIND	BLACKOUT BLIND
C2R	ZO C2R	WO C2R	MIR CXA	DUR C2R 4212
F6R	ZO F6R	WO F6R	MIR FXA	DUR F6R 4212
M4R	ZO M4R	WO M4R	MIR MXA	DUR M4R 4212
M6R	ZO M6R	WO M6R	MIR MXA	DUR M6R 4212
M8R	ZO M8R	WO M8R	MIR MXA	DUR M8R 4212
S6R	ZO S6R	WO S6R	MIR SXA	DUR S6R 4212



10 | years guarantee