

# VELUX break-glass point KFK 100



Easily activate smoke ventilation windows with the break-glass point KFK 100. Simply break the glass and push the red button to open the windows. Place additional break-glass points throughout your building for increased safety. Available in five different colours according to local requirements.

- Increase safety by adding additional break-glass points that activate the smoke ventilation system when triggered.
- Add additional wall switches, break-glass points, smoke detectors and rain sensors.
- Fully complies with current and expected future CE standards and regulations.

## Technical information

---

|                                        |                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>VELUX break-glass point KFK 100</b> | <b>Material and colour</b>         | The break glass point comes in different colours depending on product code:<br>KFK 100: grey (RAL 7035/NCS S 1000-N)<br>KFK 101: red (RAL 3000)<br>KFK 102: yellow (RAL 1004-1021)<br>KFK 103: blue (RAL 5009-5015)<br>KFK 104: orange (RAL 2011)                                                                                                                                                                                                                                                           |
|                                        | <b>Size and weight description</b> | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|                                        | <b>Installation and use</b>        | KFK 100/101/102/103/104 are all surface-mounted and must be connected according to current national legislation. The installation surface must be smooth and level. The KFK 10- must be installed in continuous single line connections to ensure completion of the line from the control unit until the last KFK is monitored. Individual connections to more than one KFK does not allow monitoring. When connecting the lead cable through the control unit, the cable must be fastened with cable ties. |
|                                        | <b>Power consumption</b>           | 12V d.c.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|                                        | <b>Compatibility</b>               | Full compatibility with VELUX smoke ventilation systems KFX and KFC 210/220                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                                        | <b>Connection</b>                  | KFK 10- is connected directly to the control unit with a 6 core cable. Min. cross section: 0.5 mm <sup>2</sup> . Max. Cable length: 100m.                                                                                                                                                                                                                                                                                                                                                                   |