


COXDOME GALAXY RANGE

The 'dome-only' solution for the refurbishment and replacement of rooflights fitted to existing kerbs and upstands

- Designed to be fitted to existing builder's kerbs
- 100mm flanged polycarbonate unit, ensures a fit with most kerbs without the need for adjustment
- Ideal for refurbishments where only glazing needs to be replaced
- Class 1 fire performance to BS476 Pt7
- Suitable for installation on a roof pitch between 0° and 15°

All sizes available in single, double, triple and quadruple skin.

Clear or diffused glazing options



Minimum 50mm builder's kerb required, ideally 100mm maximum.

IMPORTANT NOTE:

The glazing tape between the polycarbonate layers is 100mm and therefore can be visible on builder's kerbs of less than 100mm width.

All Galaxy domes are supplied with fixings, and undrilled for maximum flexibility.



Pyramids, trapezoids and circular domes are not available in the Galaxy range.



- In triple skin format, Galaxy has a U-value of 1.7W/m2K
- Manufactured using 3mm polycarbonate which achieves B-s1-d0 and therefore attains Class 1 certification (according to EN 13501-1:2007)
- Class B non-fragile to ACR[M]001

Nominal Size Chart	Min Ext Kerb	Actual Rooflight Size
600 x 600	510 x 510	640 x 640
600 x 900	510 x 810	640 x 940
600 x 1200	510 x 1120	640 x 1250
600 x 1800	510 x 1730	640 x 1860
750 x 750	660 x 660	790 x 790
750 x 900	660 x 810	790 x 940
900 x 900	810 x 810	940 x 940
900 x 1200	810 x 1120	940 x 1250
900 x 1800	810 x 1730	940 x 1860
1050 x 1050	970 x 970	1100 x 1100
1050 x 1500	970 x 1420	1100 x 1550
1200 x 1200	1120 x 1120	1250 x 1250
1200 x 1800	1120 x 1730	1250 x 1860
1200 x 2400	1120 x 2340	1250 x 2470
1500 x 1500	1420 x 1420	1550 x 1550
1800 x 1800	1730 x 1730	1860 x 1860

COXDOME is a UK manufacturer, providing natural daylight and ventilation solutions since 1954

