





Revolutionary glass rooflight to allow maximum natural light

COXDOME FLAT GLASS

- Ideal for new build and refurbishment projects
- Exceptional noise reduction
- Can be installed onto existing builder's kerbs or preformed upstand
- Uninterrupted glass surface offers pure daylight
- Clear panoramic views internally
- Clean appearance from external roofscape
- Slim aluminium frame profile
- Isolated internally for excellent thermal performance
- Toughened outer glass panel
- Fixing screws concealed with flush cover for invisibility



| External Kerb Size (mm) | Daylight Size RO16 Upstand (mm) | Daylight Size Builders Upstand (mm) |
|----------------------------|------------------------------------|--|
| 750 x 750 | 600 x 600 | 650 x 650 |
| 900 x 900 | 750 x 750 | 800 x 800 |
| 900 x 1200 | 750 x 1050 | 800 x 1100 |
| 1000 x 1000 | 850 x 850 | 900 x 900 |
| 1000 x 1500 | 850 x 1350 | 900 x 1400 |
| 1000 x 1800 | 850 x 1650 | 900 x 1700 |
| 1000 x 2000 | 850 x 1850 | 900 x 1900 |
| 1200 x 1200 | 1050 x 1050 | 1100 x 1100 |
| 1500 x 1500 | 1350 x 1350 | 1400 x 1400 |
| | | |





| Product Specification | | |
|-------------------------|---|--|
| Installation Angle | 0-7° | |
| Installation | Screws with cover strip | |
| Frame | Aluminium | |
| Coating | Powder coated aluminium slate grey (RAL 7015) | |
| Drainage | At each corner of the frame | |
| Waterproof welded | At each corner of the frame | |
| Glass assembly | 6mm toughened external | |
| Insulation (efficiency) | HR++ | |
| Insulation (U value) | 1.0 W/M ² K ⁰ | |
| Insulation (sound) | Approx 35dB | |
| Spacer | Warm edge | |
| LTA/2TA | Approx 69% / 49% | |