

AVAILABLE PRODUCTS

AVAILABLE SIZES	
C2A	55 x 78 cm
C4A	55 x 98 cm
F6A	66 x 118 cm
M4A	78 x 98 cm
M6A	78 x 118 cm
M8A	78 x 140 cm
S6A	114 x 118 cm

10year
Guarantee

ECOLITE+

ADDITIONAL VENTILATION VALVE

Our basic model, with a ventilation valve. More fresh air, without blowing away your budget.

10year
Guarantee

ECOWHITE

REINFORCED FRAME AND WHITE FINISH

A reinforced frame and fashionable white finish. An ideal combination for a contemporary interior.

10year
Guarantee

ECOVINTAGE WHITE

A PERFECT MATCH WITH CONSERVATION ROOFS

A window that meets all conservation building regulations.

10year
Guarantee

ECOSOLID

A SOLID PVC DESIGN

Our basic white PVC window. Moisture resistant and easy to maintain.

10year
Guarantee

ECOVIEW

HIGH PIVOT WINDOW

A high pivot window providing an easy escape in the event of emergency.

10year
Guarantee

ECOVIEW WHITE

HIGH PIVOT WINDOW

A high pivot window providing uninhibited exterior views and an easy escape in the event of an emergency.

Product code	DVY B900	AAV B910	CVY B911 Pine (CVY 901) also available	APY B900	MOE B1000	MOE B1010
Air permeability	Class 4	Class 4	Class 4	Class 4	Class 4	Class 4
Resistance to wind load	Class C4	Class C4	Class C4	Class C4	Class C4	Class C4
Pane construction	4-16-4H	4-16-4H	4-16-4H	4-16-4H	33.2-14-4H	33.2-14-4H
Gas	Argon	Argon	Argon	Argon	Argon	Argon
Ventilation valve	Yes	No	Yes	No	Yes	Yes
Toughened outer pane	Yes	Yes	Yes	Yes	Yes	Yes
Sound reduction	32 (-1, -5) dB	32 (-1, -5) dB	32 (-1, -5) dB	32 (-1, -5) dB	32 (-1, -5) dB	32 (-1, -5) dB
Thermal insulation parameter f pane U _g [W/m²K]	1.0 W/m²K	1.0 W/m²K	1.0 W/m²K	1.0 W/m²K	1.0 W/m²K	1.0 W/m²K
Thermal insulation parameter of window U _w [W/m²K]	1.3 W/m²K	1.3 W/m²K	1.3 W/m²K	1.3 W/m²K	1.3 W/m²K	1.3 W/m²K
Water tightness	E1350	E1350	E1350	E1500	E1500	E1500


FLASHINGS



SFX
The SFX slate flashing is applicable for flat roofing materials up to 16 mm (2 x 8 mm) thickness.



LSX
Slate flashing with one-piece side parts. Applicable for flat roofing materials up to 16 mm (2 x 8 mm) thickness.



UFX
The Liteleader UFX flashing is for installing roof windows when working with the majority of available roofing materials with a profile height of between 16 and 120 mm. This flashing is also available in black (UFX VINT).



TFX
TFX installation flashing is for installing roof windows into cor-rugated roofing materials with a profile height of between 16 and 50 mm, including slate, metal roofing tiles, and trapezoidal sheets. This flashing is also avail-able in black (TFP VINT).



UCX
The Liteleader UCX flashing can be used to install windows side by side or one above the other into the majority of available roofing materials with a profile height of 16-120 mm.



SFF VINT
For recessed installation of a single roof window into slate, profile height 16 mm (2 x 8 mm). The 40 mm deeper installation offers better energy performance and aesthetics. Suitable for a roof pitch range of 20–90°.



UFX VINT
UNIVERSAL VINTAGE
Suitable for high profiled tiles and profiled materials between 16-120 mm



TFP VINT
PLAIN TILE VINTAGE
Plain tiles profile height 0-28 mm (2x14 mm), max. length 340 mm



FRE B600+
FRE B200

OPENABLE

flat roof windows
with flat glass top unit

FEATURES

- Electrically openable window for flat roofs
- Attractive, flat glass exterior design
- Maintenance free, easy-to-wipe internal PVC surfaces
- Easy-to-clean coating on external glass
- Scratch-free, 4 mm toughened glass cover
- Laminated internal glass
- Low energy insulating glass unit (inside)
- Max. opening: 200 mm (142 mm ventilation area)
- Preinstalled rain sensor
- Hidden motor
- Wall switch controller
- Fixing screws and brackets are included
- Easy installation



FRF B600+
FRE B200

FIXED

flat roof windows
with flat glass top unit

FEATURES

- Fixed (non-openable) window for flat roofs
- Attractive, flat glass exterior design
- Maintenance free, easy-to-wipe internal PVC surfaces
- Easy-to-clean coating on external glass
- Scratch-free, 4 mm toughened glass cover
- Laminated internal glass
- Low energy insulating glass unit (inside)
- Fixing screws and brackets are included
- Easy installation

AVAILABLE SIZES

SIZE CODE	0606	0609	0808	0909
ROOF OPENING (CM)	60x60	60x90	80x80	90x90
SIZE CODE	0912	1010	1015	1212
ROOF OPENING (CM)	90x120	100x100	100x150	120x120

ACCESSORIES



FSA SOLAR BLIND FOR FLAT ROOF WINDOWS

FEATURES

- Excludes light completely
- Blocks up to extra 51% solar heat
- Wall switch is able to operate up to 200 blinds simultaneously
- Due to solar panel no wiring is needed



ROOF WINDOW ACCESSORIES


– LIVING UP HIGH MADE COMFORTABLE

A roof window is the best solution for transforming dark lofts into vibrant spaces. However, sometimes there can be too much light or you might need a little privacy. The best solution for this is one of our blinds.




DUA

Full control over the amount of light that enters your room, all the way to an almost total blackout effect. The blind is manufactured from a durable, dirt-resistant material, and its reliable guides from high-quality aluminium.




MIA

This external antiheat blind stops up to 80% of solar rays before they reach the room. It diffuses light and prevents the room overheating, without completely restricting the view.



RHA

A cost-efficient blind that lets you pleasantly diffuse the light entering your room. Can be locked in 3 different positions.



PAA

Venetian blind for roof window.



ZCA

With help of the ZCA telescopic opener rod you can easily open or close the window or the ventilation valve and operate the blackout blind or venetian blind when the window is out of reach. Can be extended up to 180 cm.



AMC

The AMC electrical opener consists of a motor unit with all of the necessary wiring, a rain sensor, and a remote controller. Its strong chain has been specifically selected to handle all sizes of roof windows, and enables opening as far as 200 mm.



Roof windows
with great functionality
and contemporary design.

Liteleader®

Naturally.