

TERMO PS





MAXIMUM LOAD



PROTECTIVE FEET



SEAL



HANDRAIL



YEARS GUARANTEE



The mark of responsible forestry





TERMO PS

The TERMO PS loft ladder has got single sealing and hatch thickness 26mm. TERMO PS model is ideally suited to conditions where the attic is insulated and does not require additional thermal insulation. This ladder is equipped with non-slip feet, which perfectly adhere to the ground and prevent scratches on the floor surface. Our non-slip feet included in TERMO PS loft ladder provide an aesthetic finish for the ladder after cutting. To increase security and for comfortable use our TERMO PS loft ladder is also equipped with stable and durable handrail. In the interest of user convenience, the handrail has been designed in such a way that it can be mounted on the left or right side depending on customer preferences. The excellent quality of materials used for the production of stairs and attention to every details of finish cause that the stairs will satisfy even the most demanding customers . The maximum load during use is up to 160 kg.

Technical specification

26 mm
20 mm
White
3 sections
135 mm
400 mm
358 mm
80 mm
134/148 cm
160/166 cm
280 cm

Box dimensions [cm] AxB

110x55 120x55 130x55 140x55 110x60 120x60 130x60 140x60 110x70 120x70 130x70 140x70

Outer box dimensions, mounting opening 2 cm larger

Non-standard dimensions

Min - Max Length 110 - 140 cm Min - Max Width 54 - 85 cm

*Unusual dimensions available in full size of untypical stairs can not exceed 1 m²

Accessories



batten






Mounting system



balustrade

Technical draw



A = 110		A > 110	
С	280 cm	С	280 cn
D	134 cm	D	148 cm
E	160 cm	E	166 cm
G	160 kg	G	160 kg