

TECHNICAL SPECIFICATION

AURORA ROOF WINDOW



Applications	Cover parts	Pane	
In public and domestic buildings	Aluminium, lacquered, RAL 7043	Construction	4-17-3
In heated, inhabited rooms	Handle	24 mm double glazing	P
In roof pitch range of 15°- 90°	Ergonomically designed moulded zinc handle, lacquered	Low E	P
Suitable on all roofings from 0 to 50 mm	Hinge	Gas (<i>argon</i>)	P
Features	Pivot hinge	Ug (<i>W/m2K</i>)	1.1
Centre pivot		Total solar energy transmittance	0.62
Slim frame		Uw (<i>W/m2K</i>)	1.5
Elegant bottom handle		Water tightness	E1050
Two passive ventilation positions via handle		Air permeability	Class 3
Easy installation		Resistance to wind load	Class C4
10 year guarantee		Sound reduction	30 (-1,-5) dB
Material Wood and finishing		Colour	
Kiln-dried laminated pine wood		Natural wood	P
Timber from PEFC certified forests			
Knot free visible surfaces			
Fungicide protection			
Acrylic lacquer			



MEASURES								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m ²
AUR C2R	55 x 72 cm	55,0 cm	71,9 cm	39,8 cm	59,0 cm	37,3 cm	53,1 cm	0,198
AUR F6R	66 x 112 cm	66,0 cm	111,9 cm	50,8 cm	99,0 cm	48,3 cm	93,1 cm	0,449
AUR M4R	78 x 92 cm	78,0 cm	91,9 cm	62,8 cm	79,0 cm	60,3 cm	73,1 cm	0,440
AUR M6R	78 x 112 cm	78,0 cm	111,9 cm	62,8 cm	99,0 cm	60,3 cm	93,1 cm	0,561
AUR M8R	78 x 134 cm	78,0 cm	133,9 cm	62,8 cm	121,0 cm	60,3 cm	115,1 cm	0,694
AUR S6R	114 x 112 cm	114,0 cm	111,9 cm	98,8 cm	99,0 cm	96,3 cm	93,1 cm	0,896

COMPATIBILITY TABLE					
SIZE CODE	FLASHING 0-50 mm	BLACKOUT BLIND	ROLLER BLIND	VENETIAN BLIND	AWNING BLIND
C2R	AURZO C2R	AURDUR CXR	AURRHR C2A	AURPAR C2A	AURMIR CXA
F6R	AURZO F6R	AURDUR F6R	AURRHR F6A	AURPAR F6A	AURMIR FXA
M4R	AURZO M4R	AURDUR M4R	AURRHR M4A	AURPAR M4A	AURMIR MXA
M6R	AURZO M6R	AURDUR M6R	AURRHR M6A	AURPAR M6A	AURMIR MXA
M8R	AURZO M8R	AURDUR M8R	AURRHR M8A	AURPAR M8A	AURMIR MXA
S6R	AURZO S6R	AURDUR S6R	AURRHR S6A	AURPAR S6A	AURMIR SXA

10 | years guarantee

