

TECHNICAL SPECIFICATION

Liteleader®

Naturally.

10year

Guarantee



ECOWHITE

VARIANT

510

PANE

Construction	4-16-4H
24 mm double glazing	•
Low E	•
Gas (argon)	•
Toughened	•
U _g (W/m ² K)	1.1
Total solar energy transmittance	0.60

WINDOW

U _w (W/m ² K)	1.4
Water tightness	E1200
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1,-5) dB

COLOUR

Natural wood	
White painted	•



White painted wood window



Toughened outer pane



4-16-4mm



15-90°



U_g 1.1 W/m²K
U_w 1.4 W/m²K



16-120 mm



0-16 mm



16-50 mm

APPLICABLE

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all roofings with proper flashing

FEATURES

- Centre pivot
- Toughened outer glass
- Elegant bottom handle
- Two passive ventilation positions via handle
- Easy installation
- 10 year guarantee

MATERIAL | WOOD AND FINISHING

- Kiln-dried laminated white painted pine wood
- Timber from FSC certified forests
- Fungicide protection
- Water based lacquer

COVER PARTS

- Aluminium, lacquered, RAL 7043

HANDLE

- Ergonomically designed moulded zinc handle, lacquered

HINGE

- Pivot hinge

MEASURES

SIZE CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m ²
C2A	55 x 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
C4A	55 x 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
F6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
M4A	78 x 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
M6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
M8A	78 x 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729
S6A	114 x 118 cm	114 cm	117,8 cm	98,8 cm	104,9 cm	96,3 cm	99 cm	0.953

FLASHING COMPATIBILITY TABLE

SIZE CODE	SLATE	TILE	UNIVERSAL	COMBI
C2A	SFXC2A	TFXC2A	UFXC2A	UCXC2A
C4A	SFXC4A	TFXC4A	UFXC4A	UCXC4A
F6A	SFXF6A	TFXF6A	UFXF6A	UCXF6A
M4A	SFXM4A	TFXM4A	UFXM4A	UCXM4A
M6A	SFXM6A	TFXM6A	UFXM6A	UCXM6A
M8A	SFXM8A	TFXM8A	UFXM8A	UCXM8A
S6A	SFXS6A	TFXS6A	UFXS6A	UCXS6A

BLIND COMPATIBILITY TABLE

BLACKOUT BLIND	ROLLER BLIND	VENETIAN BLIND	AWNING BLIND
DURC2A	RHRCXA	PARC2A	MIRCXA
DURC4A	RHRCXA	PARC4A	MIRCXA
DURF6A	RHRFXA	PARF6A	MIRFXA
DURM4A	RHRMXA	PARM4A	MIRMXA
DURM6A	RHRMXA	PARM6A	MIRMXA
DURM8A	RHRMXA	PARM8A	MIRMXA
DURS6A	RHRS6A	PARS6A	MIRSXA