

LEAD-FREE PLUS

Issue 1 – November 2012

Description: LEAD-FREE PLUS is produced from sheet Aluminium with a protective polyurethane coating on top and a butyl adhesive on the underside. Finished with a dimpled profile this unique construction ensures that the product is waterproof, durable and extremely malleable. The butyl adhesive ensures a strong permanent bond to all building materials without the need for a primer unless the surface is extremely unstable and forming a watertight joint.

Colour: Lead Coloured Grey

- Key Features:**
- Low cost
 - Versatile
 - Waterproof
 - Durable
 - Malleable
 - Lightweight
 - Easily cut
 - Easily repaired
 - No Health & Safety issues
 - Alternative to traditional lead

Application: LEAD-FREE PLUS can be applied and worked in any direction using a mallet, roller or by hand. Cutting is achieved with scissors or knife. Before fixing LEAD-FREE PLUS to any building material surface the protective paper should be left in place until the final shape and position is determined. The surface should also be clean and dry to achieve permanent adhesion. If the building material surface is unstable then Cromar Bituminous Primer should be applied. Any jointing detail should have a minimum overlap of 100mm.

Product Data:

Roll width/mm:	150	300	450
Roll length/metres:	5	5	5
Rolls/box:	1	1	1

Technical Data:

Surface Finish:	3D Dimpled
Temperature Resistance:	-40°C / +90°C
Minimum Working Temperature:	+5°C
Guarantee:	5 years
Corrosion Resistance:	Yes
Resistance to UV Degradation:	Yes

Health and Safety: Please refer to Health and Safety Data Sheet on LEAD-FREE PLUS.



CROMAR
BUILDING PRODUCTS LIMITED

Further Information: In the event of further queries or problems concerning the use of this product, please contact the address below:-

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar's products are available for sale in accordance with Cromar's Standard Terms and Conditions of Sale, which are available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our Representatives, Agents, or Distributors, as the conditions of use, and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.

Unit 3, The Maltings Industrial Estate
Doncaster Road, Whitley Bridge
North Yorkshire DN14 0HH
Tel: 01977 663133 Fax: 01977 662186
info@cromar.uk.com www.cromar.uk.com



CROMAR
BUILDING PRODUCTS LIMITED